



# RAVALENE® CR H 2041

Recycled HDPE Density Polyethylene Resin

## OVERVIEW

<b>Description</b>	Recycled Natural HDPE compound
<b>Applications</b>	Extrusion of (non-pressure) pipes, profiles & sheets. Blow molding of certain articles.
<b>Additives</b>	Standard anti-oxidant package
<b>Recycled content</b>	>98%
<b>Source</b>	Post-industrial
<b>Visual</b>	Natural

## PHYSICAL PROPERTIES

	Nominal Value (SI)	Unit	Test Method
<b>MFI (190°C / 5 kg)</b>	1	g/10 min	ISO 1133
<b>MFI (190°C/ 21.6 kg)</b>	22	g/10 min	ISO 1133
<b>Density</b>	0.95	g/cm <sup>3</sup>	ISO 1183
<b>Ash content (600 °C)</b>	0	%	ISO 3451

## EXTRUSION GUIDELINES

<b>Recommended settings</b>	Comparable processing to standard HDPE resins. Contact your local sales representative for specific advice.
-----------------------------	--

**Note:** Properties not to be construed as specifications

The information contained herein is to our knowledge accurate and reliable as of the date of publication. Ravago extends no warranties regarding fitness for a particular purpose or compliance to specifications and regulations. It is the customer's responsibility to test the product regarding suitability for a specific purpose.